## SAFETY DATA SHEET LEFRANC & BOURGEOIS SICCATIF DE COURTRAI BLANC

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

 

 PRODUCT NAME:
 LEFRANC & BOURGEOIS SICCATIF DE COURTRAI BLANC

 APPLICATIONS:
 Medium for Oil Painting

 MANUFACTURER:
 ColArt International SA 5 Rue Rene Panhard Z.I. Nord 72021 Le Mans Cedex 2

Tel: +33 2 43 83 83 00

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME			CONTENT
CAS No.:	EINECS Nr.:	CLASSIFICATION	
Zirconium carboxylate			22 %w/w
		Xi R-38	
Naphtha(Petroleum), H	lydrotreated Heavy		69 %w/w
64742-48-9	265-150-3	Xn R-10, 65, 66	

The Full Text for all R-Phrases are Displayed in Section 16

### **3. HAZARDS IDENTIFICATION**

Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

	4.	FIRST	AID	MEASURES
--	----	-------	-----	----------

INHALATION:	Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering 100% oxygen.
INGESTION:	DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Get medical attention immediately! Provide rest, warmth and fresh air.
SKIN:	Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.
EYES:	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

#### **5. FIRE FIGHTING MEASURES**

EXTINGUISHING MEDIA:	Fire can be extinguished using: Dry chemicals, sand, dolomite etc. Foam.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide (CO2). Carbon monoxide (CO).

#### 6. ACCIDENTAL RELEASE MEASURES

## **SPILL CLEANUP METHODS:** Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

#### 7. HANDLING AND STORAGE

USAGE PRECAUTIONS:	Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.
STORAGE PRECAUTIONS:	Keep in cool, dry, ventilated storage and closed containers. Keep in original container.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### **PROTECTIVE EQUIPMENT:**



VENTILATION:	Provide adequate general and local exhaust ventilation.
RESPIRATORS:	No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.
PROTECTIVE GLOVES:	Use protective gloves.
EYE PROTECTION:	Wear approved safety goggles.
<b>OTHER PROTECTION:</b>	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
HYGIENIC WORK PRACTICES:	DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. No eating or drinking while working with this material.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Liquid.		
COLOUR:	Colourless. to Yellow.		
ODOUR/TASTE:	Hydrocarbon.		
BOILING POINT (°C, interval):	> 150	Pressure:	760mmHg
DENSITY/SPECIFIC GRAVITY (g/ml):	0.9	Temperature (°C):	15
FLASH POINT (°C):	43	Method:	CC (Closed cup).

### **10. STABILITY AND REACTIVITY**

STABILITY:	Normally stable.
CONDITIONS TO AVOID:	Avoid contact with acids and oxidising substances.
HAZARDOUS DECOMP. PRODUCTS:	Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

## **11. TOXICOLOGICAL INFORMATION**

INHALATION:	Prolonged inhalation of high concentrations may damage respiratory system.
INGESTION:	Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs.
SKIN:	Acts as a defatting agent on skin. May cause cracking of skin, and eczema.
EYES:	May cause severe irritation to eyes.

## **12. ECOLOGICAL INFORMATION**

**ECOLOGICAL INFORMATION:** Not regarded as dangerous for the environment.

#### **13. DISPOSAL CONSIDERATIONS**

#### **DISPOSAL METHODS:**

Dispose of in accordance with Local Authority requirements.

#### **14. TRANSPORT INFORMATION**

#### LABEL FOR CONVEYANCE:



UN No. ROAD:	1263
UK ROAD TRANSPORT CLASS:	3
UK ROAD PACK GR.:	III
ADR CLASS No.:	3
ADR CLASS:	Class 3: Flammable liquids.
ADR PACK GR.	III
PROPER SHIPPING NAME I:	Paint related product
RID CLASS No.:	3
UN No. SEA:	1263
IMDG CLASS:	3
EmS No.:	3-05
MFAG TABLE No.:	310
UN No., AIR:	1263
ICAO CLASS:	3

### **15. REGULATORY INFORMATION**

#### LABEL FOR SUPPLY:



#### **RISK PHRASES:**

SAFETY PHRASES:

R-65 Harmful: may cause lung damage if swallowed. R-10 Flammable.R-38 Irritating to skin.S-2 Keep out of the reach of children.

S-23 Do not breathe gas/fumes/vapour/spray.

S-24/25 Avoid contact with skin and eyes.

S-62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

## **16. OTHER INFORMATION**

INFORMATION SOURCES:	Material Safety Data Sheet, Misc. manufacturers.
<b>REVISION DATE:</b>	09/04/2003
REV. No./REPL. SDS GENERATED:	1/10/03/2003
R-PHRASES (Full Text):	R-10 Flammable. R-65 Harmful: may cause lung damage if swallowed. R-66 Repeated exposure may cause skin dryness or cracking. R-38 Irritating to skin.